



## **One-touch secure transfer of data direct to CD & DVD.**

Supports popular memory formats & USB storage

Standalone – no PC required

Simple operation



The Multi Media Transfer Tower professional duplicator offers fast, efficient backup of your important data from erasable memory cards or flash drives to archival CDs and DVDs at a cost effective price. Available with up to 3 target drives, Transfer Tower copiers are perfect for data-sensitive disc production with no PC intervention for minimum security risks.

With no PC or hard drive required the Transfer Tower offers a secure and reliable duplication service. A compact and stylish design coupled with multiple memory card and USB drive readers built-in makes the Multi Media Transfer Tower the ultimate multi-functional disc duplicator.

Fitted with the latest DVD±R drives, up to 3 CDs discs can be created simultaneously in less than 3 minutes and 3 DVDs in less than 7 minutes.

Intelligent Multi-Session and Disc Spanning Technologies make data transfer as easy as one touch of a button.

Rigorously tested for performance and reliability, Multi Media Transfer Towers are manufactured to strict quality control standards, delivering enhanced duplication at every level.



Function:

Multimedia CD/DVD Duplication System

**MS Slot:** MS, MS-Duo, MS Pro, MS Pro Duo, MS MagicGate, MS Pro MagicGate, MS-Duo MagicGate, MS Pro Duo MagicGate etc.

**CF Slot:** CF I, CF II, IBM Micro Drive

Supported Source Formats:

**SD Slot:** SD, SD Pro, Mini SD\*, Mini SD Pro\*, Micro SD\*, SD HS, Wi-Fi SD, Super HS SD (\*Adaptor Required)

**MMC Slot:** MMC, MMC Pro, MMC II, RS-MMC

**Discs:** DVD-ROM, DVD-Video, DVD±R/RW, DVD±DL, CD-ROM, CD-I, Audio CD, Video CD, Bootable CD, Mixed-mode CD, Multi-session CD, CD-Plus, Business Card CD, Mini CD-R

Media Handling:

DVD±R/RW, DVD+R DL, CD-R/RW, Business card CD, 3" Mini CD-R

Targets:

Up to 3 targets

Drives:

(up to) 3x DVD±R, 1x DVD-ROM

Maximum Write Speeds:

18x DVD±R/48xCD-R

Voltage:

115V or 230V

Operating Temperature:

41°F ~ 104°F

Operating Humidity:

20% ~ 80%

Regulations:

FCC, CE, UL, RoHS

Operation:

No PC Required



## Warranty

12 months back to base, all parts and labour included.  
2<sup>nd</sup> year excludes drives and carriage.  
Extended warranties also available.